Distributed by:

GP Batteries

WORLDWIDE HEADQUARTERS
GPI INTERNATIONAL LIMITED

Gold Peak Building, 8/F, 30 Kwai Wing Road, Kwai Chung, N.T., Hong Kong
Tel: (852) 2484 3333 Fax: (852) 2480 5912
Email: gpii@goldpeak.com Website: www.gpbatteries.com

SALES AND MARKETING BRANCH OFFICES

Asean

Singapore
GP BATTERY MARKETING (SINGAPORE) PTE. LIMITED
97 Pioneer Road, Singapore 639579
Tel: (65) 6559 9760 Fax: (65) 6559 9761
Email: sales_sg@gpbatteries.com.sg

Malaysia
GP BATTERY MARKETING (MALAYSIA) SDN. BHD.
Lot 8, Jalan Pemberita U1/49,
Temasya Industrial Park, 40150 Shah Alam,
Selangor Darul Ehsan, Malaysia
Tel: (60) 3 5569 3499 Fax: (60) 3 5569 3498
Email: gpbmm@gpbatteries.com.sg

Thailand
GP BATTERY MARKETING (THAILAND) CO., LTD.
106 Soi Sukhumvit 26, Sukhumvit Road,
Klongton, Klongtoey, Bangkok 10110, Thailand
Tel: (66) 2 260 1318 Fax: (66) 2 260 1315
Email: thaicontact@gpbatteries.com.sg

China

Huizhou
HUIZHOU CHAO BA BATTERIES COMPANY LIMITED
No. 29, 6th Gaoxin Road,
Zhongkai Gaoxin Industrial Zone,
Huizhou City, Guangdong, China
(Postal code: 516006)
Tel: (86) 752 263 8698 Fax: (86) 752 263 8666
Email: gpconsumer@gpbatteries.com.cn
Website: www.gpbatteries.com.cn

Shanghai
GP BATTERY MARKETING (SHANGHAI) LIMITED
3F, South of the Huidian Business Building,
No. 694 Quxi Road Huangpu District,
Shanghai, China
(Postal code: 200023)
Tel: (86) 21 6336 0966 Fax: (86) 21 6336 0807
Email: terrence_ho_sh@gpbatteries.com.cn

Hong Kong

GP BATTERY MARKETING (H.K.) LIMITED
3/F, Gold Peak Building, 30 Kwai Wing Road,
Kwai Chung, N.T., Hong Kong.
Tel: (852) 2420 0281 Fax: (852) 2494 9349
Email: gpbmhk@goldpeak.com
Website: www.gpbatteries.com.hk

VECTRIX INTERNATIONAL LIMITED
4/F, Gold Peak Building, 30 Kwai Wing Road,
Kwai Chung, N.T., Hong Kong.
Tel: (852) 2484 3447 Fax: (852) 2484 1362

Taiwan

GOLD PEAK INDUSTRIES (TAIWAN) LIMITED - TAIPEI OFFICE
8/F, No. 148, Sec. 1, Xingsheng South Road,
Zhongzheng Dist., Taipei 10061, Taiwan.
Tel: (886) 2 2398 5598 Fax: (886) 2 2393 5551 / 2 2393 5552
Email: ls_ho@goldpeak.com

GWA ENERGY, INC.,
4F, 27-1, Lane 169, Kangning St., Sijhih
Taipei, Taiwan ZIP 22180
Tel: (886) 2-8695 1756 Fax: (886) 2-8695 1259
Email: billiou@gwaenergy.com
Website: www.gwaenergy.com

South Korea

GP BATTERY MARKETING (KOREA) LIMITED
5/F, WhaDeok Building, 319-11, Yangjae-Dong,
Seocho-Gu, Seoul, South Korea
Tel: (82) 2 549 7188 / 549 7189 Fax: (82) 2 514 0623
Email: jh_baak@goldpeak.com
Website: www.gpbattery.co.kr

Europe

Russia
AZ LIMITED
Building 4, vlad. "Tricolor", mic. dist. Vostryakovo,
Domodedovo, Moscow Region, Russia 142072
Prospekt Andropova 18, korp. 5, floor 18
Moscow, Russia, 115432
Tel/Fax: (7) 495 926 5050
Website: www.gpbatteries.ru

Poland
DANISH POLISH BATTERIES SP. Z.O.O.
ul. Zielona 22,
83-200 Starogard Gdansk, Poland
Tel: (48) 58-56 001 52/55 Fax: (48) 58-56 001 56
Email: W_Orlowski@gpbattery.com.pl

GP BATTERY (POLAND) SP Z.O.O.
ul. Łopuszańska 36,
02-220 Warszawa, Poland
Tel: (48) 22 500 9500 / 868 0490 Fax: (48) 22 846 7535
Email: gpbp@gpbattery.com.pl
Website: www.gpbattery.pl

Netherlands
GP BATTERIES EUROPE B.V.
Kortijzer 4, NL-5721 VE Asten,
The Netherlands
Tel: (31) 493 681030 Fax: (31) 493 681039
Email: info@gpbatteries-europe.com
Website: www.gpbatteries-europe.com

UK
GP BATTERIES (UK) LIMITED
Monument View, Chelston Business Park,
Wellington, Somerset, TA21 9ND, United Kingdom
Tel: (44) 1823 660044 Fax: (44) 1823 665595
Email: sales@gpbatteries.co.uk
Website: www.gpbatteries.co.uk

France
GP BATTERY MARKETING FRANCE SA
ZAE du Trou Grillon - BP 49
91280 Saint Pierre du Perray, France
Tel: (33) 1 6989 6200 Fax: (33) 1 6989 6210
Email: info@gpbatteries.fr
Website: www.gpbatteries.fr

Germany
GP BATTERY MARKETING (GERMANY) GMBH
Schiessstrasse 68, D-40549 Dusseldorf, Germany
Tel: (49) 211 5229540 Fax: (49) 211 52295454
Email: info@gpbatteries.de
Website: www.gpbatteries.de

Italy
GP BATTERY MARKETING ITALY S.R.L.
Via. Alessandro Volta 3,
20090 Assago (Mi), Italy
Tel: (39) 02 488 2512 Fax: (39) 02 488 2865
Email: gpbatteries@gpbatteries.it
Website: www.gpbatteries.it

Sweden
GPBM NORDIC AB
Argongatan 2 B, SE-431 53,
Molndal, Sweden
Tel: (46) 31 799 1600 Fax: (46) 31 799 1601
Email: info@gpbmnordic.se
Website: www.gpbmnordic.se

US & Latin America

GOLD PEAK INDUSTRIES (NORTH AMERICA) INC.
11235 West Bernardo Court,
San Diego, CA92127-1638, U.S.A.
Tel: (1) 858 674 6099 Fax: (1) 858 674 6496 / 674 5883
Email: gpina@gpina.com
Website: www.gpina.com

GP BATTERY MARKETING (LATIN AMERICA) INC.
8370 NW, 66th Street, Miami,
Florida 33166, U.S.A.
Tel: (1) 305 471 7717 Fax: (1) 305 471 7718
Email: gpmiami@gpmiami.com

Canada

GP BATTERY MARKETING INC.
Unit 7, 7780 Woodbine Avenue,
Markham, Ontario, Canada L3R 2N7
Tel: (1) 905 474 9507 Fax: (1) 905 474 9452
Email: Oliver@gpbattery.com
Website: www.gpbattery.com

GP BATTERY MARKETING INC. – B.C. Office
Unit 822, 5300 No. 3 Road,
Lansdowne Centre
Richmond, B.C. Canada V6X 2X9
Tel: (1) 604-231 9905 Fax: (1) 604-231 9953
Email: gpbmbc@shawbiz.ca
Website: www.gpbattery.com

Middle East

GP BATTERY MARKETING MIDDLE EAST LIMITED FZC
P.O. Box 7989, M4-02, Saif Zone,
Sharjah, United Arab Emirates
Tel: (971) 6 5578787 Fax: (971) 6 5578777
Email: md_pme@emirates.net.ae

GPPA8PB-A 09/12 All rights reserved. No parts of this catalogue written or pictorial may be reproduced without the permission of GPI International Ltd.

GP Batteries

Product Portfolio

PowerBank + Rechargeable Batteries

STAYING AHEAD WITH GP Batteries

As an expert principally engaged in the development, manufacturing and marketing of rechargeable and primary battery products, GP Batteries is one of the world's leading battery manufacturers and the no.1 in Asia outside of Japan.

To keep up with the fast-moving hi-tech world and the rocketing popularity of power hungry electronic devices, GP Batteries has a comprehensive range of chargers and the best-in-class Nickel Metal Hydride rechargeable batteries to meet users' needs.

Each of these high performance, feature-packed GP PowerBank is ready to stun tech fans with an exciting blend of stylish design and outstanding capabilities. Cost-efficient and environmentally friendly, there's no doubt they are the indispensable for every household.

Known for its superior products and quality reliability, GP Batteries is the major back-up provider for leading electronic manufacturers. It has marketing and trading offices all over Asia, North and South America, Europe and Middle East

Keeping to the fore of progress in the almost daily changing innovative world of high-tech, GP Batteries is the consumers' No.1 battery manufacturer for portable electronics and the retailers' guarantee of product reliability.

INDEX

PREMIUM SERIES — P 4-7

FAST SERIES — P 8-9

MID-RANGE SERIES — P 10-16

STANDARD SERIES — P 17-24

SPECIALTY SERIES — P 25

NiMH RECHARGEABLE BATTERIES — P 30-32

ReCyko⁺ — P 34-35

PB80

V800C PowerBank

- 15 mins to charge up 2 pcs NiMH batteries
- Digital clock
- Easy check 3-color LED icons to show charging status
- Safe standby switch to initiate charging process
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use

PB60

V600D PowerBank

- 1 hour to charge up 2 pcs NiMH batteries
- Easy check LCD display to show charging status
- Safe standby switch to initiate charging process
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use

4 x 2700 series AA

4 x 2500 series AA

4 x 2700 series AA

4 x 2500 series AA

PB65

H650C PowerBank

- 1 hour to charge up 4 pcs NiMH batteries
- Digital clock
- Easy check 3-color LED icons to show charging status
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use
- DC12V car charging function (optional)

PB50

H500 PowerBank

- 2 hours to charge up 2 pcs NiMH batteries
- Battery ejector to easily unload batteries
- Easy check 3-color LED icons to show charging status
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs of NiMH AA or AAA in any combinations
- Primary & bad battery detection
- AC100-240V for EU / UK version, AC 100-120V for US version
- DC12V car charging function (optional)

4 x 2700 series AA

4 x 2500 series AA

4 x 2700 series AA

4 x 2500 series AA

PB70

PB70 PowerBank

- 2 hours to charge up 1 to 4 pcs NiMH AA or AAA batteries
- 60% reduction in carbon emissions
- Saves 45% energy during charging
- Automatic energy saving mode when charging completed
- Compact design, minimize material production
- LED indicators glow underneath to show charging status
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- AC 100-240V worldwide use

PB14

SMART 2 PowerBank

- 1 hour to charge up 4 pcs NiMH batteries
- 4 LED indicators
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs NiMH AA or AAA in any combinations
- GP Patented Smart Recharge Technology
- Primary & bad battery detection
- AC100-240V worldwide use
- DC12V car charging function (optional)

4 x 2100 series AA

4 x 850 series AAA

4 x 2700 series AA

4 x 2500 series AA

3HRS CHARGING TIME

PB550

PB550 PowerBank

- 3 hours to charge up 2 to 4 pcs NiMH AA or AAA batteries
- Auto cut-off safety control by temperature and time to prevent overcharging
- Two charging channels, can charge 2 or 4 pcs NiMH AA or AAA
- Primary & bad battery detection
- Car charging function
- LED indicators
- AC100-240V worldwide use

6HRS CHARGING TIME

PB570

PB570 PowerBank

- 6 hours to charge up 4 pcs NiMH AA or AAA batteries
- Auto cut-off safety control by temperature and time to prevent overcharging
- Two charging channels, can charge 2 or 4 pcs NiMH AA or AAA
- Primary & bad battery detection
- LED indicators
- AC100-240V worldwide use

4 x 2700 series AA

4 x 2500 series AA

4 x 2700 series AA

4 x 2500 series AA

PB560

5HRS CHARGING TIME

PB560 PowerBank

- 5 hours to charge up 2 pcs NiMH AA or AAA batteries
- Auto cut-off safety control by temperature and time to prevent overcharging
- Individval charging channels can charge 1 or 2 NiMH AA or AAA
- Primary & bad battery detection
- LED indicators
- AC100-240V worldwide use

PB540

3HRS CHARGING TIME

M540 PowerBank

- 3 hours to charge up 1 to 4 pcs NiMH AA or AAA batteries
- Ultra compact and lightweight
- Detachable adaptor plugs (US, EU & UK) for traveller convenience
- Dual color LED indicator
- Auto cut-off safety control by voltage, temperature and time to prevent overcharging
- Individual charging channels, can charge 1-4 pcs NiMH AA or AAA in any combinations
- Primary battery & bad battery detection
- AC100-240V worldwide use

2 x 2700 series AA

2 x 2500 series AA

4 x 2700 series AA

4 x 2500 series AA

PB25

MINI QUICK PowerBank

- 5 hours to charge up 2 pcs NiMH batteries
- Slim and compact design
- Dual color LED indicator
- Auto cut-off safety control by temperature and time to prevent overcharging
- Individual charging channels, can charge 1 or 2 pcs NiMH AA or AAA
- Primary & bad battery detection
- AC100-240V worldwide use

2 x 2700 series AA

2 x 2500 series AA

PB27

QUICK 3 PowerBank

- 8 hours to charge up 4 pcs NiMH batteries
- USB output port for charging electronic devices
- Ultra slim design
- Dual color LED indicator
- Auto cut-off safety control by temperature and time to prevent overcharging
- Two charging channels, can charge 2 or 4 pcs NiMH AA or 2 pcs NiMH AAA
- Primary & bad battery detection
- AC100-240V worldwide use

4 x 2700 series AA

4 x 2500 series AA

MEGA PowerBank

- 6 hours to charge up 8 pcs NiMH batteries
- Slim and unique design
- Two dual color LED indicators
- Auto cut-off safety control by temperature and time to prevent overcharging
- Two charging channels, can charge 4 or 8 pcs NiMH AA or AAA

PB22

4 x 1800 series AA

PB11

NITE-LITE PowerBank

- Always plug-in design for instant energy
- Built-in night light function
- Two charging channels, can charge 2 or 4 pcs NiMH AA or AAA
- Additional charging slots for 1 or 2 pcs NiMH 9V batteries
- Two LED indicators

4 x 1800mAh AA

4 x 1300mAh AA

PB410

PB410 PowerBank

- Unique design
- Two charging channels, can charge 1-2 pcs NiMH AA or AAA batteries
- Two LED indicators

2 x 1800 series AA

2 x 1300 series AA

PB420

PB420 PowerBank

- Unique design
- Two charging channels, can charge 2 or 4 pcs NiMH AA or AAA batteries
- Two LED indicators

4 x 1800 series AA

4 x 1300 series AA

PB350

S350 PowerBank

- Always plug-in design for instant energy
- Unique design
- Two charging channels, can charge 2 or 4 pcs NiMH AA or AAA batteries
- Two LED indicators

S360 PowerBank

- Always plug-in design for instant energy
- Unique design
- Two charging channels, can charge 1-2 pcs NiMH AA or AAA batteries
- Two LED indicators

PB360

4 x 1800mAh AA

4 x 1300mAh AA

2 x 1800mAh AA

2 x 1300mAh AA

PB330

PB330
PowerBank

- Always plug-in design for instant energy
- Two charging channels can charge 1 or 2pcs NiMH AA or AAA
- Two LED indicators

2 x 1800mAh AA

2 x 1300mAh AA

PB19

UNIVERSAL
PowerBank

- Universal for household use
- Charge all sizes of batteries
- Automatic charging current selection
- Two charging channels, can charge 2 or 4 pcs NiMH AA, AAA, C or D
- Additional charging slots for 1 or 2 pcs NiMH 9V batteries
- 3 LED indicators

PB320

PB320 PowerBank

- Charge 1 to 4pcs of AA,AAA,C,D and 1 to 2 pcs of 9V NiMH rechargeable batteries
- Built-in timer function for charging in predetermined time
- Discharging function to refresh the battery
- Battery tester function to test the battery condition

PB09

SPECIALTY PowerBank

- Special design for charging 9V batteries
- Charge 1 or 2 pcs NiMH 9V
- Two LED indicators

KB04

UNIVERSAL PowerBank

- Compatible with all 3.6V, 3.7V,7.2V7.4V lithium ion batteries for digital camera, camcorder, mobile phone and NiMH AA/AAA batteries
- Adjustable battery contacts with easy-to-read contact indicators for different profile of rechargeable Li-ion battery
- LED indicator displays charging status
- Automatic battery type and voltage and time
- Primary and damaged battery detection

2 x 170mAh 9V

Premium Series

Fast Series

	PowerBank V800C	PowerBank V600D	PowerBank H650C	PowerBank H500	PowerBank Eco-friendly charger	PowerBank Smart-2
Model Number	GPPB80	GPPB60	GPPB65	GPPB50	GPPB70	GPPB14
Charging Time	~15 mins	~1-2 Hours	~1 Hour	~2-4 Hours	~1-2.5 Hours	~1 Hour
Charging Channel	4 Channels	4 Channels	4 Channels	4 Channels	4 Channels	4 Channels
Configuration	Corded Type	Corded Type	Corded Type	Corded Type	Plug-In Type	Corded Type
Input Voltage	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz (EU/UK) 100-120V AC 60Hz (US)	100-240V AC 50/60Hz	100-240V AC 50/60Hz 12V DC
Output Voltage	DC 12V 3.3A	DC 12V 1A	DC 12V 1.5A	DC 1.6V	DC 1.42V	DC 12V 1.5A
Battery Type	NiMH	NiMH	NiMH	NiMH	NiMH	NiMH
Battery Size	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA	4 x AA/AAA
Car Charging Function	✓	✓	✓	✓	—	✓
Charging Current						
-AA	1-2 pcs - 7000mA 3-4 pcs - 4000mA	1-2 pcs - 2200mA 3-4 pcs - 1100mA	2000mA	1-2 pcs - 1150mA 3 pcs - 766mA 4 pcs - 575mA	1000mA	2000mA
-AAA	3400mA	1100mA	1000mA	1-2 pcs - 475mA 3 pcs - 317mA 4 pcs - 237.5mA	450mA	1000mA
Trickle Charge	✓	✓	✓	✓	✓	✓
Termination Method						
- Minus Delta Voltage (-dV)	Individual	Individual	Individual	Individual	Individual	Individual
- Safety Timer	Individual	Individual	Individual	Individual	Individual	Individual
- Temperature Protection	Individual	Individual	Individual	Individual	Individual	Individual
- Alkaline Battery Detection	✓	✓	✓	✓	✓	✓
- Damaged Battery Detection	✓	✓	✓	✓	✓	✓
LED Indicator	3-Color Icons x 7	3-Color Icons x 7	3-Color Icons x 7	3-Color Icons x 7	Green LED x 4	Orange x 4
Safety Approval or Compliance	GS/CE/UL/ FCC	GS/CE/UL/ FCC/Energy Star	GS/CE/UL/ FCC/Energy Star	GS/CE/UL/PSE FCC/Energy Star	GS/CE/ETL/FCC Energy Star	GS/CE/UL/FCC/ SAA/Energy Star
Dimension (L)x(W)x(T) mm	126 x 38 x 89.5	126 x 38 x 89.5	125 x 75 x 29	116 x 72.5 x 32	102.4 X 66.8 X 28	115 x 80 x 31.5

Mid-Range Series

	PowerBank PB550	PowerBank PB570	PowerBank PB560	PowerBank M540	PowerBank M540
Model Number	GPPB550	GPPB570	GPPB560	GPPB540	GPPB25
Charging Time	~2-6 Hours	~3.5-7 Hours	~3-6 Hours	~3 Hours	~5 Hours
Charging Channel	2 Channels	2 Channels	2 Channels	4 Channels	2 Channels
Configuration	Corded Type	Plug-in Type	Plug-in Type	Plug-in Type Foldable US plug Detachable UK & EU plugs	Plug-in Type Foldable US Plug
Input Voltage	100-240V AC 50/60Hz 12V DC	AC100-240V 50/60Hz	AC100-240V 50/60Hz	100-240V AC 50/60Hz	100-240V AC 50/60Hz
Output Voltage	DC 2.8V 1050mA	DC 1.4V	DC 1.4V	DC 1.4V	DC 1.4V
Battery Type	NiMH	NiMH	NiMH	NiMH	NiMH
Battery Size	4 x AA/AAA	4 x AA/AAA	2 x AA/AAA	4 x AA/AAA	2 x AA/AAA
Car Charging Function	✓	--	--	--	--
Charging Current					
-AA	2 pcs - 1050mA 4 pcs - 525mA	400mA +/- 10%	500mA	600mA	500mA
-AAA	2 pcs - 525mA 4 pcs - 525mA	160mA	220mA	600mA	220mA
Trickle Charge	✓	✓	✓	✓	✓
Termination Method					
- Minus Delta Voltage (-dV)	✓	✓	✓	Individual	--
- Safety Timer	✓	✓	✓	✓	✓
- Temperature Protection	✓	✓	✓	Individual	✓
- Alkaline Battery Detection	✓	✓	✓	✓	✓
- Damaged Battery Detection	✓	✓	✓	✓	✓
LED Indicator	Amber LED x 2	Amber LED x 2	Amber LED x 2	Dual color x 1	Dual color x 1
Safety Approval or Compliance	GS/CE/ETL/FCC	GS/CE/ETL/FCC	GS/CE/ETL/FCC	GS/CE/UL/FCC	GS/CE/ETL/FCC/ Energy Star
Dimension (L)x(W)x(T) mm	108 x 75 x 36.3	108 x 75 x 36.3	108 x 43 x 36.3	75.1 x 64 x 37.3	107 x 48 x 36

Mid-Range Series

Standard Series

	PowerBank Quick 3	PowerBank Mega	PowerBank Nite-Lite	PowerBank PB410	PowerBank PB420
Model Number	GPPB27	GPPB22	GPPB11	GPPB410	GPPB420
Charging Time	~8 Hours	~6 Hours	~10 Hours	~13 Hours	~13 Hours
Charging Channel	2 Channels	2 Channels	2 Channels	2 Channels	2 Channels
Configuration	Plug-in Type Foldable US plug	Corded Type	Plug-in Type Foldable US plug	Plug-in Type	Plug-in Type
Input Voltage	100-240V AC 50/60Hz	230V AC 50Hz (EU) 240V AC 50Hz (UK) 120V AC 60Hz (US)	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)	230V AC 50Hz (GS/BS) 120V AC 60Hz (US)	230V AC 50Hz (GS/BS) 120V AC 60Hz (US)
Output Voltage	DC 2.8V (AA/AAA) DC 5V 500mA (USB output)	DC 5.6V	DC 2.8V (AA/AAA) DC 9V (9V)	DC 1.4V	DC 1.4V
Battery Type	NiMH	NiMH	NiMH	NiMH	NiMH
Battery Size	4 x AA 2 x AAA	8 x AA/AAA	4 x AA/AAA 2 x 9V	2 x AA/AAA	4 x AA/AAA
Charging Current					
-AA	360mA	500mA	220mA	180mA	180mA
-AAA	160mA	200mA	85mA	180mA	180mA
-9V	--	--	24mA	--	--
Trickle Charge	✓	✓	--	--	--
Termination Method					
- Minus Delta Voltage (-dV)	--	--	--	--	--
- Safety Timer	✓	✓	--	--	--
- Temperature Protection	✓	✓	--	--	--
- Alkaline Battery Detection	✓	--	--	--	--
- Damaged Battery Detection	✓	--	--	--	--
LED Indicator	Dual color x 1	Dual color x 2	Green x 2	Amber LED x 2	Amber LED x 2
Safety Approval or Compliance	GS/CE/ETL/FCC/ Energy Star	GS/CE/UL/FCC	GS/CE/UL/FCC	GS/CE/ETL/FCC	GS/CE/ETL/FCC
Dimension (L)x(W)x(T) mm	119 x 79.8 x 32	116 x 90 x 31	110.5 x 73 x 45	108 x 43 x 33.3	108 x 75 x 33.3

Standard Series

Specialty Series

	PowerBank S350	PowerBank S360	PowerBank S330	PowerBank Universal	PowerBank S320	PowerBank Specialty	PowerBank Universal
Model Number	GPPB350	GPPB360	GPPB330	GPPB19	GPPB320	GPPB09	GPKB04
Charging Time	~11 Hours	~11 Hours	~6.5-13.5 Hours	D: 2200mAh~5 Hours; 7000mAh~16 Hours C: 2200mAh~5 Hours; 3500mAh~10 Hours AA: 1300mAh~5 Hours; 2000mAh~10 Hours AAA: 600mAh~5 Hours; 800mAh~9 Hours 9V: 170mAh~16 Hours	D:2200mAh~9Hours; 4500Ah~15Hours C:2200mAh~9Hours; 3500Ah~15Hours AA: 1300mAh~6Hours; 1800mAh~9Hours AA: 2100mAh~9Hours; 2700mAh~15Hours AAA: 600mAh~3Hours; 1000mAh~6Hours 9V: 170mAh~15Hours	~10 Hours	Li-ion:1~4Hours; NiMH:3~8Hours
Charging Channel	2 Channels	2 Channels	2 Channels	2 Channels	2 Channels	2 Channels	2 Channels
Configuration	Plug-in Type	Plug-in Type	Plug-in Type	Corded Type	Corded Type	Plug-in Type	Corded Type
Input Voltage	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)	230V AC 50Hz (GS) 120V AC 60Hz (UL) 100 - 240V AC 50/60Hz	230V AC 50Hz (EU) 240V AC 50Hz (UK) 120V AC 60Hz (US)	230V / 50Hz (EU/UK)	230V AC 50Hz (EU/UK) 120V AC 60Hz (US)	100 - 240V AC 50/60Hz 12V DC
Output Voltage	DC 2.8V	DC 1.4V	DC 1.4V	D/C/AA/AAA: DC 2x 2.8V 9V: DC 2x 9V	D/C/AA/AAA: DC 4x12V 9V: DC 2x 9V	DC 9.8V	DC 12V 1A
Battery Type	NiMH	NiMH	NiMH	NiMH	NiMH	NiMH	NiMH / Li-ion
Battery Size	4 x AA/AAA	2 x AA/AAA	2 x AA/AAA	4 x D/C/AA/AAA 2x9V	4 x D/C/AA/AAA 2x9V	2 x 9V	1 x Li-ion 2 x AA/AAA
Charging Current							
-D	--	--	--	560mA	270mA	--	--
-C	--	--	--	440mA	270mA	--	--
-AA	200mA	200mA	180mA	260mA	270mA	--	500mA
-AAA	100mA	100mA	70mA	120mA	270mA	--	500mA
-9V	--	--	--	14mA	13mA	24mA	--
Trickle Charge	--	--	✓	--	✓	--	--
Termination Method							
- Minus Delta Voltage (-dV)	--	--	--	--	--	--	✓
- Safety Timer	--	--	--	--	✓	--	✓
- Temperature Protection	--	--	--	--	--	--	--
- Alkaline Battery Detection	--	--	--	--	--	--	--
- Damaged Battery Detection	--	--	--	--	--	--	--
LED Indicator	Red x 2	Red x 2	Red x 2	2 Green for 2 Channels; 1 Green for 9V	Dual Color x 4 Green x 1 Orange x 1	Green x 2	Dual Color x 1
Safety Approval or Compliance	GS/CE/UL/FCC	GS/CE/UL/PSE/ FCC	GS/CE/FCC/ETL	GS/CE/UL/FCC	GS/CE	GS/CE/UL/FCC	GS/CE/UL/BS
Dimension (L)x(W)x(T) mm	105 x 44 x 46	105 x 44 x 34.5	101 X 37 X 33.2	178 x 97 x 57	210 x 105 x 59	98.6 x 66.2 x 60	94.7 x 59.7 x 30

GP Rechargeable

Takes up to 1970 shots**

***Performance may vary under different operating conditions*

Good for All Applications

MP3 Players / CD Players

Digital Cameras

Torches

Toys (Racing Cars)

Environmentally Friendly

Stays Charged longer

Great Savings

AAA

2 x 100AAAHC 1.2V

2 x 85AAAHC 1.2V

2 x 65AAAHC 1.2V

4 x 100AAAHC 1.2V

4 x 85AAAHC 1.2V

4 x 65AAAHC 1.2V

AA (Low Self Discharge)

2 x 270AAHC 1.2V

2 x 250AAHC 1.2V

2 x 210AAHC 1.2V

2 x 180AAHC 1.2V

2 x 130AAHC 1.2V

4 x 270AAHC 1.2V

4 x 250AAHC 1.2V

4 x 210AAHC 1.2V

4 x 180AAHC 1.2V

4 x 130AAHC 1.2V

C

2 x 350CHC 1.2V

2 x 220CH 1.2V

D

2 x 900DHC 1.2V

2 x 700DHC 1.2V

2 x 450DHC 1.2V

2 x 220DH 1.2V

9V

1 x 17R8H 8.4V

Cell Size	Model No.	Nominal Voltage (V)	Capacity (0.2C discharge)*(mAh) Minimum	Capacity (0.2C discharge)*(mAh) Typical	Nominal Dimension (mm) Diameter	Nominal Dimension (mm) Height	Weight (g)	Standard Charge Current (mA)	Standard Charge Time (Hour)	1 Hr Charge Current (mA)#
NICKEL METAL HYDRIDE SERIES										
AA	GP270AAHC**	1.2	2550	2600	14.5	50.5	31.5	255	16	2550
	GP250AAHC**	1.2	2450	2450	14.5	50.5	31.0	245	16	2450
	GP210AAHC**	1.2	2000	2050	14.5	50.5	28.0	200	16	2000
	GP180AAHC**	1.2	1800	1850	14.5	50.5	28.0	180	16	1800
	GP130AAHC**	1.2	1300	1340	14.5	50.5	25.0	130	16	1300
AAA	GP100AAAHC	1.2	930	970	10.5	44.5	15.2	93	16	930
	GP85AAAHC	1.2	850	870	10.5	44.5	14.2	85	16	850
	GP65AAAHC**	1.2	650	680	10.5	44.5	13.0	65	16	650
C	GP350CHC	1.2	3500	3500	26.2	50.0	78.5	350	16	Not Applicable
	GP220CH	1.2	2200	2200	26.2	50.0	61.0	220	16	Not Applicable
D	GP900DHC	1.2	9000	9000	34.2	61.5	173.0	900	16	Not Applicable
	GP700DHC	1.2	7000	7000	34.2	61.5	155.0	700	16	Not Applicable
	GP450DHC	1.2	4500	4500	34.2	61.5	130.0	450	16	Not Applicable
	GP220DH	1.2	2200	2200	34.2	61.5	71.0	220	16	Not Applicable
9V	GP17R8H**	8.4	170	175	15.7(T)X26.5(W)X48.5(H)		32.0	17	16	170

One hour rate with charge termination control. * After charging at 0.1 C for 16 hours. ** With UL approval.

GP ReCyko+

Pre-charged rechargeable battery

Stays charged longer



* Applicable to AA & AAA

Great Savings
Can be recharged and reused up to 1,000 times.

Environmentally Friendly
GP ReCyko+ contributes to the environment through greatly reducing battery disposal, answering modern customer's demand for more environmentally friendly goods.

Complies with IEC standard

Good for All Applications

MP3 Players / CD Players

Digital Cameras

Torches

Toys (Racing Cars)

AA

2 x 210AAHCB 1.2V

4 x 210AAHCB 1.2V

AAA

2 x 85AAAHCB 1.2V

4 x 85AAAHCB 1.2V

C

2 x 300CHCB 1.2V

2 x 260CHB 1.2V

D

2 x 570DHCB 1.2V

2 x 260DHB 1.2V

9V

1 x 15R8HB 8.4V

GP ReCyko+ SERIES

Cell Size	Model No.	Nominal Voltage (V)	Capacity (0.2C discharge)*(mAh) Minimum	Capacity (0.2C discharge)*(mAh) Typical	Nominal Dimension (mm) Diameter	Nominal Dimension (mm) Height	Weight (g)	Standard Charge Current (mA)	Standard Charge Time (Hour)	1 Hr Charge Current (mA)#
AA	GP210AAHCB**	1.2	2000	2050	14.5	50.5	30	200	16	2000
AAA	GP85AAAHCB**	1.2	800	820	10.5	44.5	14	80	16	800
C	GP260CHB	1.2	2600	2600	26.2	50.0	62	260	16	2600
	GP300CHCB	1.2	3000	3000	26.2	50.0	70	300	16	3000
D	GP260DHB	1.2	2600	2600	34.2	61.5	72	260	16	2600
	GP570DHCB	1.2	5700	5700	34.2	61.5	124	570	16	5700
9V	GP15R8HB	8.4	150	155	15.7(T)X26.5(W)X48.5(H)		32	15	16	150

One hour rate with charge termination control * After charging at 0.1 C for 16 hours ** With UL approval